



L151924330

LED Ba15s Tube T18x45mm 10-24V 250Lm
3W 3000K 830 360° DC Helder Niet-Dimbaar

Marine & Industrie, Tubular VR 10-24V



General		Energy	
Eprel registration no	1113045	Operating voltage	24 V
Socket	Ba15s	Volt	10..24 V
Bulb shape	T18	Frequency	50..60 Hz
Width	18.00 mm	Watt	3 W
Depth	18.00 mm	Current type	DC
Height	45.00 mm	Power factor	1
Finish	Clear	Energy efficiency class	G
Colour	Colourless	Energy consumption	3 W
Body material	Polycarbonat	Lamp efficacy	83.33
Lifespan	30000 hours		
Switches	50000	LED	
Beam angle	360 °	Filament LED	No
Dimmable	No	LED type	SMD 2835
Degree of protection	IP20	Dimm type	Non-Dim
Net weight	0.011 kg	Number of leds / sticks	24
Warranty	2 years	Colour consistency SDCM	SDCM3
		Dim to warm	No
		Adjustable beam angle	No
Light		Ordering details	
Kelvin	3000 K	L151924330	Quantity pc(s) EAN
Colour temp nr	830	Single package	1 8718739066519
Stable lumen	250 lm	Outer carton	100 28718739066513
Color Rendering Index (CRI)	80		

