PROFESSIONAL LIGHTING

L267035030

LED Bay15d Tube T17x52mm 230V 380Lm 3.5W 3000K 830 360° AC Helder Niet-Dimbaar

Marine & Industrie, Tubular Short

General	
Eprel registration no	2498084
Socket	Bay15d
Bulb shape	T17
Width	17.00 mm
Depth	17.00 mm
Height	52.00 mm
Finish	Clear
Colour	Colourless
Body material	Polycarbonat
Lifespan	15000 hours
Switches	50000
Beam angle	360 °
Dimmable	No
Degree of protection	IP20
Net weight	0.016 kg
Warranty	2 years

Light	
Kelvin	3000 K
Colour temp nr	830
Stable lumen	380 lm
Color Rendering Index (CRI)	80

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	3.5 W
Current type	AC
Power factor	0.5
Energy efficiency class	F
Energy consumption	4 W
Lamp efficacy	108.57

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	32
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Ordering details		
L267035030	Quantity pc(s)	EAN
Single package	1	8718739083127
Inner carton	10	18718739083124
Outer carton	100	28718739083121

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal