

# STELLA ROUND WALL GU10 6W CCT

SLI003060CCT\_PW

LED luminaire STELLA ROUND WALL GU10 6W CCT for replaceable light source with the possibility of changing the light color (CCT), with a power of 6 W. Thanks to the ability to change the color temperature (CCT) in the range 3000 / 4000 / 6000K, we can adjust the light color depending on our needs and preferences. It has a high IP44 rating, making it ideal for use in areas of high humidity. IK08 class provides impact resistance. Wide beam angle of illumination 270° ensures even illumination of the surface.

CCT

IP44

IK08



|                 |                     |
|-----------------|---------------------|
| Power           | <b>6 W</b>          |
| Luminous flux*  | <b>450 lm (90°)</b> |
| Colour of light | <b>CCT</b>          |
| Socket          | <b>GU10</b>         |

|                    |                             |
|--------------------|-----------------------------|
| Voltage            | <b>230 V</b>                |
| Colour temperature | <b>3000 / 4000 / 6000 K</b> |
| Beam angle         | <b>270 °</b>                |
| IK                 | <b>08</b>                   |

## Technical data

|                              |                      |
|------------------------------|----------------------|
| Code                         | SLI003060CCT_PW      |
| Power                        | 6 W                  |
| Nominal current              | 45 mA                |
| Voltage                      | 230 V                |
| Energy consumption           | 6 kWh/1000h          |
| Frequency                    | 50HZ Hz              |
| Protection class             | II                   |
| Power factor                 | 0.5                  |
| Useful luminous flux*        | 450 lm (90°)         |
| Lamp efficacy                | 75 lm/W              |
| Colour temperature           | 3000 / 4000 / 6000 K |
| Colour of light              | CCT                  |
| Beam angle                   | 270 °                |
| RA                           | 80                   |
| Light source included        | Yes                  |
| Uniformity of color SDCM max | 5                    |
| Dimmable                     | No                   |
| Working temperature range    | -20 / +40 °          |
| Lifespan                     | 17000 h              |
| Housing material             | POLIWĘGLAN           |
| Socket                       | GU10                 |
| IK                           | 08                   |
| Degree of protection (IP)    | IP44                 |
| Colour                       | Gray                 |
| Dimension (AxBxC)            | 155x160x230 mm       |
| For use                      | Outside / Inside     |
| Assembly method              | On the ceiling       |
| Application                  | INT / EXT            |
| Made in                      | PRC                  |
| Other                        | Funkcja CCT ,        |

## Logistics data

|                       |          |
|-----------------------|----------|
| Bulk packaging        | 10 pcs.  |
| Quantity per pallet   | 150 pcs. |
| Gross weight (1 pcs.) | 7.02 kg  |

## Related documents

 User manual Declaration of Conformity

