

# SLI055012\_PW

NOCTIS TECHNIC FLOODLIGHT 30W CW 230V IP65 303x230x43mm YELLOW 2 YW SPECTRUM

IP65

IK07



Power **30 W**  
Colour temperature **6000 K**  
Beam angle **100 °**  
Degree of protection (IP) **IP65**

Voltage **230 V**  
Colour of light **CW**  
IK **07**

## Technical data

|                              |                                       |
|------------------------------|---------------------------------------|
| Code                         | SLI055012_PW                          |
| Power                        | 30 W                                  |
| Nominal current              | 130 mA                                |
| Voltage                      | 230 V                                 |
| Energy consumption           | 30 kWh/1000h                          |
| Frequency                    | 50HZ Hz                               |
| Protection class             | I                                     |
| Power supply included        | +                                     |
| Power factor                 | 0.980000                              |
| Useful luminous flux*        | 2500 lm (120°)                        |
| Luminous flux                | 2500 lm (360°)                        |
| Lamp efficacy                | 83 lm/W                               |
| Colour temperature           | 6000 K                                |
| Colour of light              | CW                                    |
| Beam angle                   | 100 °                                 |
| RA                           | 80                                    |
| Light source included        | Yes                                   |
| Uniformity of color SDCM max | 5                                     |
| Dimmable                     | No                                    |
| Working temperature range    | 20 / +40 °                            |
| Warranty                     | 2 years                               |
| Lifespan                     | 17000 h                               |
| (On/Off)                     | 15000                                 |
| Housing material             | aluminum                              |
| IK                           | 07                                    |
| Degree of protection (IP)    | IP65                                  |
| Colour                       | Czarny / żółty                        |
| Dimension (AxBxC)            | 188x130x30 (303x230x43 with frame) mm |
| For use                      | Outside                               |
| Assembly method              | On the ceiling                        |
| Application                  | EXT                                   |
| Made in                      | PRC                                   |


## Logistics data

|                       |          |
|-----------------------|----------|
| Bulk packaging        | 10 pcs.  |
| Quantity per pallet   | 300 pcs. |
| Gross weight (1 pcs.) | 1.05 kg  |

\*applies to the LED source used

## Related documents



 Declaration of Conformity